

**Stoner** Molding Solutions<sup>®</sup>  
You Mold It. We Release It.

# Stoner<sup>®</sup> E206 Silicone Mold Release<sup>™</sup>



## Product Description

Stoner<sup>®</sup> E206 Silicone Mold Release<sup>™</sup> is specially formulated as a food grade release agent and anti-stick lubricant for molded materials such as plastics, rubber, waxes, and similar materials. Provides fast, easy part removal from molds and multiple part releases per application. Improves molding efficiency in many processes including injection, compression, transfer, vacuum form, pour cast, die cast, and extrusion molding.

### E206 Silicone Mold Release<sup>™</sup> ADVANTAGES:

- Saves time by allowing molded parts to be removed quickly and easily from molds.
- Improves part appearance and reduces defects caused by sticking.
- Formulated to provide high levels of user and environmental safety.
- Contains no Class I (CFC) or Class II (HCFC) Ozone Depleting Substances.
- Contains no chlorinated solvents such as 1,1,1 trichloroethane or methylene chloride.
- The silicone in E206 meets FDA regulation 21 CFR 181.28 as a release agent in the manufacture of food contacting materials.
- Colorless and non-staining.

## Uses

Stoner<sup>®</sup> E206 Silicone Mold Release<sup>™</sup> is a grade release agent and anti-stick lubricant for molded materials:

- Plastics
- Waxes
- Rubber

## Direction for Use

### Recommended Procedure

Shake well. Hold can 10 to 12 inches from mold surface. Apply a thin mist coating on mold surface for best results.

## Storage and Handling

Do not puncture or incinerate container. Do not expose container to heat or store at temperatures above 120 °F. Keep container away from and do not use near sparks, open flame, heated surfaces, or other ignition sources.

## Packaging

Stoner<sup>®</sup> E206 Silicone Mold Release<sup>™</sup> is available in:

- 12-can case of 12 oz cans  
Part # E206
- 5-gallon pails & 55-gallon drum  
Part # M203 (Solvent Based)
- 5-gallon pails & 55-gallon drum  
Part # P203 (Water Based)
- 37-pound Giant Aerosol  
Part # E606

## Technical Assistance

Call: 800-227-5538 or 1 (717) 786-7355  
Email: [CustomerService@StonerSolutions.com](mailto:CustomerService@StonerSolutions.com)  
Visit: [StonerMolding.com](http://StonerMolding.com)

**NO RISK GUARANTEE.** Stoner Molding guarantees 100% satisfaction or your money back. If you're ever dissatisfied with any Stoner Molding product, simply return the unused portion for a full refund.



DAI GLOBAL  
ISO 9001  
Quality

[StonerMolding.com](http://StonerMolding.com)

1070 Robert Fulton Hwy. • Quarryville, PA 17566 • 1-800-227-5538 • 1-717-786-7355



# Safety Data Sheet

## E206 Silicone Mold Release™

# Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

### 1. IDENTIFICATION

Stoner Incorporated  
1070 Robert Fulton Hwy.  
Quarryville, PA 17566  
1-800-227-5538

Product Name: Silicone Mold Release™  
Product Code: E206  
Product Use: Mold Release  
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

### 2. HAZARD IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;  
GHS Hazard Symbols



**MPK ENTERPRISES**  
5082 Bolsa Ave. #105 - Huntington Beach, CA 92649  
ph# (714) 899-7963 fax# (714) 899-7965  
[www.hobbysilicone.com](http://www.hobbysilicone.com)

**GHS Classification** Gases under pressure - Liquefied Gas  
Flammable Aerosol Category 2

**Signal Word** Warning

**Hazard Statements** Flammable aerosol.  
Contains gas under pressure; may explode if heated.

**Precautionary Statements**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.

**Storage** Protect from sunlight. Store in a well-ventilated place.  
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent	
Halogenated hydrocarbon/ether blend	Mixture	80-100	
HMIS® III* HAZARDOUS WARNINGS:			
Health: 1	Flammability: 2	Physical: 2	Personal Protective Equipment: See Section 8

\* See [www.paint.org/hmis](http://www.paint.org/hmis) or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

### 4. FIRST AID MEASURES

**Eyes:** Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

**Skin Contact:** In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. For liquid contact, treat for frostbite if necessary. Seek medical attention if symptoms persist. Wash clothing before reuse.

**Ingestion:** Ingestion is an unlikely route of exposure. Contact a physician, medical facility, or poison control center for advice on whether to induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness or is unconscious or convulsing.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

#### NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

Stoner Incorporated

E206

PAGE 1

## 5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions.

Fire Fighting Instructions: Use CO<sub>2</sub>, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

## 6. ACCIDENTAL RELEASE MEASURES

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. If runoff occurs, notify authorities as required.

## 7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. May cause frostbite.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.

Respiratory Protection: A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Halogenated hydrocarbon/ether blend	Mixture	Not established	Not established	1000ppm TWA (Mfr.)

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Aerosol can	Lower Flammability Limit (%):	Not applicable
Appearance:	Clear Colorless	Upper Flammability Limit (%):	Not applicable
Odor:	Slight ethereal.	Vapor Pressure (PSIG @ 70°F):	78.00
Odor Threshold:	Mild	Vapor Density [air = 1]:	>1
pH:	Not applicable	Relative Density (H <sub>2</sub> O=1):	0.8
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Negligible; 0-1%
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	Not applicable	Autoignition Temperature (°F):	Not applicable
Evaporation Rate:	No data available	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	40 - 60		

## 10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Alkali. Alkaline earth metals. Freshly abraded aluminum surfaces. Powdered metals. Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers. Acetic acids Organic acid anhydrides.

Decomposition Products: This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride. If heated with peroxides present, violent decomposition can occur. When heated to temperatures above 150°C in the presence of air, one of the ingredients in this product can form formaldehyde vapors. Formaldehyde vapor is harmful by inhalation; irritating to eyes; sensitizer to the respiratory system; an acute toxicant and a potential cancer hazard at concentrations greater than 0.75 ppm.

## 11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity: No data available.

IARC Carcinogen Designation: No data available

Ingredient  
No data available

CAS #

Toxicological Data

**12. ECOLOGICAL INFORMATION**

Ecological Toxicity: No data available  
 Mobility: No data available

<b>Ingredient</b>	<b>CAS #</b>
Ether propellant	115-10-6

**Toxicological Data**  
 48HR NOEC GUPPIES > 4000 mg/L  
 48HR NOEC Daphnia > 4000 mg/L  
 No data available

**13. DISPOSAL CONSIDERATIONS**

Disposal : Dispose according to Federal, State and local regulations.

**14. TRANSPORTATION INFORMATION**

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

**15. REGULATORY INFORMATION**

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

**Toxic Substances Control Act**

All components of this product are listed on the TSCA inventory.

**California Prop 65**

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

**16. OTHER INFORMATION**

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 7/7/2021

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.